


Apex Xavier II+ Spec

简介 Brief

米文Apex Xavier II+ 是一款嵌入式人工智能计算机，能够为众多终端设备赋予人工智能计算力，从而有效降低人工智能产品的落地门槛。Apex Xavier II+ 可以在满足抗振防水等工业级标准的同时，提供高达32Tops计算能力，能够很好的满足低速无人驾驶等场景的视觉计算需求。除此之外Apex Xavier II+ 还可提供高效的多传感器时钟同步功能。

MiiVii Apex Xavier II+ is an embedded AI supercomputer. It delivers massive computing capabilities and essential features to terminal devices. With shock resistance connector and waterproof design, MiiVii Apex Xavier II+ is suitable for outdoor usage. In addition, MiiVii Apex Xavier II+ offers clock synchronization function.



特性 Features

- IP65 防护等级^{注1}

IP65 Protection

- 高效主动式风扇散热

High performance active fan cooling system

- 8×GMSL2视频输入接口

8×GMSL2 Camera supported

- -25℃-70℃工作温度


-25℃-70℃ Operating temperature

- 内部提供MINI PCIE与 M.2 2280接口拓展

MINI PCIE Slot and M.2 2280 Slot

注1：设备有防尘放水处理，如客户自行安装扩展模块存在困难，建议选购时预装相应扩展模块。

产品外观 Appearance



产品规格 Specifications

处理器模组 Processor

	Specification
Processor	NVIDIA Jetson AGX Xavier 32GB
AI Performance	Up to 32T OPS
CPU	8-core ARM v8.2 64-bit CPU
GPU	512-core Volta GPU
Memory	32GB 256-Bit LPDDR4
DL Accelerator	2×NV DLA Engines
Storage	32GB eMMC 5.1
Video Encode	4x 4Kp60 8x 4Kp30 16x 1080p60 32x 1080p30 (H.265) 4x 4Kp60 8x 4Kp30 14x 1080p60 30x 1080p30 (H.264)

Video Decode	2x 8Kp30 6x 4Kp60 12x 4Kp30 26x 1080p60 52x 1080p30 (H.265) 4x 4Kp60 8x 4Kp30 16x 1080p60 32x 1080p30 (H.264)
--------------	---

接口 I/O

接口Interface	规格/Specifications
网络接口Network	4× Gigabit Port（可选配IEEE 802.3 at PoE+ 25.5W）
相机接口Camera	2× GMSL2 4 IN 1 MINI FAKRA TYPE（10V,Transmission distance up to 15 meters,GMSL2 compatible with GMSL1）
视频输出Video output	1× HDMI 2.0（TYPE A）
USB	2× USB 3.0（TYPE A）
通用输入/输出口GPIO	4× In（0-12V） 4× Out（3.3V）
CAN FD	5× CAN FD（With CAN chip Terminal resistor 120）
串口UART	1×Debug（RS232）， 3×RS232， 2×RS485/RS422
同步输入/输出口Sync I/O	1×SYNC_IN（0-12V）， 1×SYNC_OUT（3.3V）， 1×SYNC_PPS（3.3V）
扩展接口User Expansion	1× M.2 M Key（PCIe x4, 2280）， 1× Mini PCIe（For 4G or WiFi expansion）， 1× Nano SIM Socket
按键Function Key	1×Power KEY, 1×Reset KEY, 1×Recovery KEY（Button）

供电 Power Supply

Power Supply	Spec
Input Type	DC
Input Voltage	Wide input 9-36V DC
Typical consumption	30W

结构 Mechanical

Mechanical	Spec
Dimensions (W×D×H)	276mm×214mm×68mm(I/O ports and mounting holes included) 240mm×173mm×68mm(I/O ports and mounting holes excluded)
Weight	3.5Kg

环境 Environmental


Environmental	Spec
Operating Temperature	-25℃-70℃
Storage Temperature	-40℃-80℃
Storage Humidity	10%-90% non-condensing
Vibration	2Grms,10Hz~500Hz,1h/axis
Protection	IP5X（默认） IP65 ¹ （可选）


1. Apex Xavier II+ 接口的接头选型均为IP65级别。若对整体产品有高防水要求则需要在购买时联系米文动力要求进行产品防水预处理。

尺寸及安装 Install Dimension


Apex Xavier II+ 主体尺寸及安装孔位尺寸如图:

Dimensions and mounting hole position as below:





左视图 Left view(Unit:mm)



安装孔位图 Mounting Hole(Unit:mm)

